



How to change the battery in a secure way

1/. Back up any data or software you may have installed on the Meazura™ by performing a Hotsync® operation using the Palm Desktop software or use the Card backup utility to backup to your CF card if you have one.

2/. Power down the Meazura™ by following one of the three methods below. Note: All data will be lost on the SDRAM!

- *Method 1* - If you already have a ROM504 or later installed, execute the *Device Info* application. Tap the *title bar* or *drop down menu icon* to pull down the menu. Tap the *Power Down System* item, followed by *Yes, Proceed* to power down.
- *Method 2* - Turn off the Meazura via the *On/Off* button. Press and hold the *down arrow* button down. Now simultaneously press and hold the *On/Off* button down. The Meazura will turn on for approx. 8 seconds and then power down.

3/. Remove the battery clip (if available) by using a tool such as pliers.

4/. Remove the battery and replace it with the new one.

5/. Re-place the battery clip – Ensure the rubber gasket is present

6/. System will reboot with a hard reset. If not, please proceed with a manual hard reset (refer to chapter 6 resetting of the quick start guide provided in the kit box)

You can also download the quick start guide from the following link:

http://www.aceeca.com/downloads/download_overview.php/cPath/1/downloads_id/10

7/. Once system is up and running, you can restore the contents from the Compact Flash Card or from PC.

If you encounter any technical issues, please contact techsupport@aceeca.com